



LIGHT MATERIAL BUCKET BML


TECHNICAL SPECIFICATIONS

- 1 Bolted and reversible underplate (option)
- Bucket bottom anti-rubbing bands

DESCRIPTION

Bucket for loading light materials complete with central reinforcement. Each model can be equipped with a bolted and reversible underplate. Ideal for loading material with low specific weight such as snow, cereals, feed, silage for biogas, etc.






MODELS		BML 1700	BML 1900	BML 2100	BML 2300	BML 2450
Width	mm	1716	1916	2116	2316	2450
Depth	mm	1025	1025	1025	1250	1450
Height	mm	984	984	984	1090	1202
SAE capacity	m ³	1,00	1,20	1,50	1,75	2,50
Weight without linkage	Kg	265	282	298	450	750
	Tons	1,7÷5,5	1,8÷6,2	2÷7,2	3,3÷10	5,5÷15

OPTIONS

- 1** Bolted and reversible underplate

LINKAGE SYSTEMS

-  Universal linkage for Skid-Steer Loader
-  Non universal linkage for Skid-Steer Loader
-  Wheel Loaders, Backhoe Loaders and Telehandlers linkage

APPLICATIONS

- SNOW COLLECTION IN URBAN AREAS
- ZOOTECHNY
- AGRICULTURAL SECTOR
- RECYCLING PLANTS
- COMPOSTING PLANTS
- BIOMASS POWER PLANTS
- BIOGAS PLANTS

