



GRAPPLE FORK


FPRA

TECHNICAL SPECIFICATIONS

- 1 Forks safety removable protection
- 2 Double grip actioned by two hydraulic cylinders
- 3 Blocking valve so to hold in safe and secure manner

DESCRIPTION

Grapple fork with **double grip** ideal for safely loading large quantities of material thanks to the presence of a **blocking valve**. The standard equipment is completed by bolted forks and flexible hoses. Each model is suitable to be matched at Skid-Steer Loaders, small articulated Wheel Loaders, Backhoe Loaders and Telehandlers.



MODELS		FPRA 1400	FPRA 1550	FPRA 1680	FPRA 1800	FPRA 2030
Width	mm	1420	1570	1700	1820	2030
Weight without linkage	Kg	265	297	313	330	365
Forks' length	mm	700	700	700	700	700
Forks	nr	9	10	11	11	15
	Tons	0,9÷4	1,5÷5	2÷6,5	2,7÷7	3÷8

LINKAGE SYSTEMS

-  Universal linkage for Skid-Steer Loader
-  Non universal linkage for Skid-Steer Loader
-  Wheel Loaders, Backhoe Loaders and Telehandlers linkage

APPLICATIONS

- AGRICULTURAL SECTOR
- LANDSCAPING
- GARDENING
- ZOOTECHNY
- BIOMASS POWER PLANTS
- PUBLIC GREEN MAINTENANCE



3

