

TECHNICAL SPECIFICATIONS

- Set up for bolted linkage systems
- 2 Shock-resistant and anticavitation valve
- 3 Bidirectional hydraulic motor
- 4 Strong and compact reinforced body with clinging edges
- 5 Sides designed for easy sliding

1 2 3 of the wood, can have from 60 to 100 mm. diameters. 4 LEMME) [*] SHAFT SET UP ON **DEMAND:** IT'S POSSIBLE TO EQUIP THE MULCHING HEAD TT WITH KNIVES OR HAMMERS KIT, EXCEPT THE TT60 MODEL, EQUIPPED WITH KNIVES

The Mulching Head TT can be equipped with "Y" knives composed by 3 double cut blades or with Hammers kit [*]. Thanks to a bidirectional hydraulic motor each TT model is not provided by sliding roller while the slippage on the ground is ensured by the design of the sides. The application of a shock-resistant and anti-cavitation valve avoid the connection to the the drainage line (except TT 130 model). All models are equipped by flexible hoses and set up for bolted linkage plate. Since they are specifically designed for industrial machines'application such as mini-midi excavators and backhoe loader's arms, the mulching head TT by U.Emme don't fear any competition: they can be used for grass mowing, finely shredded by triple knives, for mulching operations, made easy from the wide inlet mouth, and also in grinding shrubs and young trees that, depending on the tenacity





MODELS		TT 60	TT 80	TT 100	TT 130
Working width	mm	642	790	1034	1300
Total width	mm	950	1100	1360	1700
Weight without linkage	Kg	95	150	220	400
Knives / hammers kit	nr	16	16	20	20
Maximum oil flow	1/1'	35	55	55	80
Maximum pressure	bar	210	210	210	210
	Tons	1÷3	3÷4,5	4,5÷6	6÷12
Apr	Tons	1,5÷3,5	3,5÷4,5	4,5÷6	6÷12

TOOLS

6 Knives Kit

Hammers kit

OPTIONS

8 Bolted floating interface

LINKAGE SYSTEMS

- **9** Standard bolted plate
- Naked plate for quick couplers

APPLICATIONS

- SHREDDING PRUNING RESIDUES IN ORCHARDS, VINEYARDS, ETC.
- GREEN MAINTENANCE
- SHREDDING STRAW, CORN STALKS OR OTHERS OPEN FIELD CROPS
- DITCHES AND DIKES CLEANING
- LAWN MOVING
- CLEANING OF WOODED AREAS
- LANDSCAPING
- GARDENING









